

ANSUL® NFF 3x3 UL201 3%x3% Non-Fluorinated Foam Concentrate

Features

- Designed in accordance with NFPA Standard 11 for Low-, Medium-, and High-Expansion Foam
- UL 162 listed as a synthetic alcohol resistant foam concentrate for use on hydrocarbon and polar solvent fuel fires
- Passes UL 162 type III test protocol on hydrocarbons at a design application rate of 0.10 gpm/ft² (4.1 Lpm/m²)
 - Recommended for use at 0.10 gpm/ft² (4.1 Lpm/m²) for spill fire applications
- Effective control and suppression on hydrocarbon fuels
- Superior drain time with a longer lasting foam blanket for better burnback resistance and post-fire suppression
- EN1568:2018 – Parts 3 and 4
- GreenScreen Certified™ Silver firefighting foam concentrate

Description


ANSUL® NFF 3x3 UL201 is a 3%x3% Alcohol Resistant Non-Fluorinated Foam Concentrate that provides excellent fire and vapor suppression for Class B, polar solvent and hydrocarbon fuel fires. This synthetic foam concentrate is intended for forceful or gentle firefighting applications at 3% solution on hydrocarbon fuels and gentle firefighting applications at 3% solution on polar solvent fuels.

ANSUL® NFF 3x3 UL201 foam solution utilizes three suppression mechanisms intended for rapid fire knockdown and superior burnback resistance:

- The foam blanket has extended drain times to help block oxygen to the fuel and suppress fuel vapor.
- On polar solvent fires, liquid drains from the foam blanket and forms a polymeric membrane which protects the foam from destruction by the polar fuel, suppresses vapors, and seals the fuel surface.
- The water content of the foam solution produces a cooling effect for additional fire suppression.

ANSUL® NFF 3x3 UL201 concentrate is a non-fluorinated firefighting foam concentrate, meaning that it does not have any intentionally added PFAS chemistry and is produced in equipment that has not handled PFAS chemistry.

ANSUL® NFF 3x3 UL201 concentrate thus complies with Directives (EU) 2017/1000 on PFOA and 2019/1021 (EU POPs directive).



011518

Table 1: Typical physiochemical properties

Appearance	Viscous yellow liquid
Density	1.04 ± 0.02 g/ml
pH	7.0 to 8.0
Refractive index	1.365 minimum
Viscosity*:	1790 ± 250 cPs at 60 rpm
Viscosity*:	2900 ± 500 cPs at 30 rpm
Freeze Point**:	24 °F (-4 °C)
Storage and operating range:	35 °F to 120 °F (2 °C to 49 °C)

*Brookfield Viscometer Spindle #4

**In accordance with EN1568:2018 protocol

ANSUL® NFF 3x3 UL201 Foam Concentrate is a non-Newtonian fluid that is both pseudoplastic and thixotropic. Due to these properties, dynamic viscosity decreases as shear increases.

Application

ANSUL® NFF 3x3 UL201 Foam Concentrate is intended for use on both types of Class B fires: hydrocarbon fuels with low water solubility, such as crude oils, gasolines, diesel fuels, and aviation fuels; and polar solvent fuels with appreciable water solubility, such as methyl and ethyl alcohol, acetone, and methyl ethyl ketone. The concentrate has excellent wetting properties that can effectively combat Class A fires. It may also be used in conjunction with dry chemical agents to provide even greater fire suppression performance.

ANSUL® NFF 3x3 UL201 Foam Concentrate is well-suited for use in applications such as municipal and industrial response for spill and limited scale Type III hazards as well as foam systems with Type II discharge devices. Examples of these applications include:

- Industrial chemical and petroleum processing facilities
- Truck/rail loading and unloading facilities
- Flammable liquid containment areas
- Mobile equipment

Application (Continued)

Table 2: Application rates

Fuel group	Concentration	Minimum recommended application rate	
		gpm/ft ²	(Lpm/m ²)
Type III Application¹ – UL Listed			
Hydrocarbons	3%	0.16	(6.5)
E15	3%	0.17	(6.9)
Type III Application² – Third Party Witnessed			
Hydrocarbons	3%	0.10	(4.1)
Premium gasoline	3%	0.16	(6.5)
Type II Application³ – UL Listed			
Hydrocarbons	3%	0.10	(4.1)
Alcohols	3%	0.17	(6.9)
Ethanol (EtOH)	3%	0.10	(4.1)
Ketones	3%	0.17	(6.9)
E85	3%	0.15	(6.1)
1. TYPE III DISCHARGE OUTLET – A device that delivers the foam directly onto the burning liquid as described in UL 162.			
2. NFPA 11 allows a design rate of 0.10 gpm/ft ² (4.1 Lpm/m ²) for spill fire applications. This product has been tested in accordance with UL 162 for use at this application rate.			
3. TYPE II DISCHARGE OUTLET – A device that delivers foam onto the burning liquid and partially submerges the foam or produces restricted agitation of the surface as described in UL 162.			

Foaming properties

ANSUL® NFF 3x3 UL201 Foam Concentrate may be effectively applied using most conventional foam discharge equipment at the correct dilution with fresh, salt, or hard water.

Table 3: Typical foam characteristics*

Water type:	Fresh	Salt
Proportioning rate:	3%	3%
Expansion ratio:	≥ 7:1	≥ 6:1
25% drain time (min:sec)	≥ 40:00	≥ 35:00
50% drain time (min:sec)	≥ 60:00	≥ 50:00

Note: *In accordance with EN 1568-3: 2008 protocol.

Proportioning

The recommended operational temperature range for ANSUL® NFF 3x3 UL201 Foam Concentrate is 35 °F to 120 °F (2 °C to 49 °C) per UL 162. This foam concentrate can be correctly proportioned using most conventional, properly calibrated, in-line proportioning equipment such as:

- Balanced and in-line balanced pressure pump proportioners
- Balanced pressure bladder tanks and ratio flow controllers
- Around-the-pump type proportioners
- Fixed or portable in-line venturi type proportioners
- Handline nozzles with fixed eductor/pick-up tubes

Storage and handling

ANSUL® NFF 3x3 UL201 Foam Concentrate should be stored in the original supplied package (HDPE totes, drums, or pails) or in the recommended foam system equipment as outlined in Johnson Controls Technical Bulletin Storage of Foam Concentrates. The concentrate should be maintained within the recommended operational temperature range. Freezing of the product should be avoided.

Factors that affect the foam concentrate's long-term effectiveness include temperature exposure and cycling, storage container characteristics, air exposure, evaporation, dilution, and contamination. The effective life of ANSUL® NFF 3x3 UL201 Foam Concentrate can be maximized through optimal storage conditions and correct handling. ANSUL® foam concentrates have demonstrated effective firefighting performance with contents stored in the original package under correct conditions for more than 10 years. This product should not be mixed with other types of foam concentrates or other manufacturer's foam concentrates under any circumstances. The use of multiple, separately applied finished foam products for incident response is appropriate.

Inspection

ANSUL® NFF 3x3 UL201 Foam Concentrate should be inspected periodically in accordance with NFPA 11, EN 13565-2, or other relevant standard. A representative concentrate sample should be sent to Johnson Controls Foam Analytical Services or other qualified laboratory for quality analysis per the applicable standard. An annual inspection and sample analysis is typically sufficient, unless the product has been exposed to unusual conditions.

Ordering information

Table 4: Ordering information

Part No.	Description	Shipping weight
Pails		
452611*	5 gal (19 L)	45 lb (20.4 kg)
452611E**	5 gal (19 L)	45 lb (20.4 kg)
Drums		
452613*	55 gal (208 L)	495 lb (224.5 kg)
452613E**	55 gal (208 L)	495 lb (224.5 kg)
Totes		
452615*	265 gal (1003 L)	2463 lb (1117 kg)
452615E**	265 gal (1003 L)	2463 lb (1117 kg)
Notes: *Manufactured in the United States of America **Manufactured in Europe Totes are not UL approved packaging.		

Safety Data Sheets (SDS) are available at www.ansul.com

If any foam product is discharged into the environment, efforts should be made to control, contain and collect the discharge for proper disposal, while following all applicable laws, regulations, and codes. Further information regarding the use, discharge, and disposal of firefighting foams can be found at www.ansul.com.

Note: While NFF (also known as SFFF) agents may be compatible with existing AFFF and/or NFF hardware, system contamination from fluorinated agents may exist if hardware and piping is not replaced upon conversion to non-fluorinated agents.

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

The GreenScreen Certified Logo and word marks are certification marks of Clean Production Action, Inc.

ANSUL® and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.